

MATS 3G Specifications

CHARACTERISTICS	MATS 3G 12 KHZ	MATS 3G 34 KHZ
Frequency band	10-15 kHz	30-39 kHz
Secured bit rates (coding included)	20 bit/s, 100 bit/s, 200 bit/s	20 bit/s, 150 bit/s, 300 bit/s
High bit rates (without coding)	850 bit/s, 2100 bit/s, 3600 bit/s, 5500 bit/s, 7400 bit/s	1000 bit/s, 3000 bit/s, 6400 bit/s, 9200 bit/s, 13000 bit/s, 16500 bit/s, 24600 bit/s
Coding efficiency	0,43	
Maximal range (low noise environment)	15 km	5 km
Power supply	18 VDC - 36 VDC standard 36 VDC - 60 VDC on request 90 VAC - 230 VAC with rack	
Power consumption	Up to 75W in transmission (185dB ref 1 µPa/1m) 0,6W in reception 40mW in stand-by	
User link	RS232 : 38400Bd (standard, configurable) RS422 on request	
Maximal depth	6000 m	
Temperature range	Working: -10°C to +50°C Storage: -20°C to +70°C	
Dimensions	L 366mm x Ø 100mm (container) Diam. 135mm (head without flange)	L 356 mm x Ø 100 mm
Dimension - Transducer head (OEM version)	L 109 mm x Ø 135 mm	L 100 mm x Ø 120 mm
Dimension - Electronic box (OEM version)	L 194 mm x Ø 80 mm	L 206 mm x Ø 80 mm

Note: Sercel reserves the right to change its specifications without prior notice.
All specifications are typical at 20°C

Sercel - France

16 rue de Bel Air
B.P. 30439 - 44474 CARQUEFOU Cedex
Téléphone: (33) 2 40 30 11 81
E-mail: sales.nantes@sercel.com
SAS au capital de 2 000 000 €
Siège Social: 16 rue de Bel Air - 44470 CARQUEFOU
378.040.497 R.C.S. Nantes Code APE 2651B

Sercel Inc. - U.S.A.

17200 Park Row
Houston, Texas 77084
Telephone: (1) 281 492 6688
E-mail: sales.houston@sercel.com

www.sercel.com
© Sercel 03/20



Ahead of the CurveSM